

**KERNOW RESOURCES
& DEVELOPMENTS LTD.**

Trading Symbol: **KRD** (TSX Venture Exchange)

Rua de Diogo Afonso, 71, Hab. 26
Porto 4150-254
Portugal

Telephone No.: 011 (351) 93 676 0927
Facsimile No. 011 (351) 22 609 5185
e-mail at: piran@mindspring.com

NEWS RELEASE

DATE: 06 December, 2007

**KERNOW REPORTS SAMPLING RESULTS FROM TWO PRIOR DRILL HOLES AT
THE ALTO SOBRIDO GOLD ANTIMONY PROJECT, PORTUGAL**

Mr. Alan Matthews, President of Kernow Resources & Developments Ltd. and Mr George Heard, President of Global Minerals Ltd. (collectively the “Companies”) are pleased to provide the following update regarding the Alto Sobrido Gold and Antimony project located in Northern Portugal. The Alto Sobrido property is located some 16 kilometres east of the city of Porto and covers an area of approximately 16.0 square kilometres.

Previous owners of the property Connary Minerals PLC (Connary) drilled two diamond drill holes at Alto Sobrido in May of 2002 : DDAS-1 and DDAS-2. The core from these two holes is stored at the INETI facility (Instituto Nacional de Engenharia, Tecnologia e Inovação) in Porto. Kernow has undertaken re-sampling by splitting the remaining half core of the main mineralised zones in both holes. The ¼ core was then sent to OMAC Laboratories in Ireland for assay.

Significant results from the re-assay program are as follows:

Hole DDAS-1

- **1.65 meters grading 3.33 % antimony from 49.75 meters to 51.40 meters**
- **2.40 meters grading 3.11 % antimony from 69.50 meters to 71.90 meters**
- **2.10 meters grading 2.54 % antimony from 78.90 meters to 81.00 meters**

Hole DDAS-2

- **2.40 meters grading 11.46 % antimony from 35.35 meters to 37.75 meters**

True width of the veins in Hole DDAS-1 are believed to be in the region of 1.0 to 2.0 meters and in DDAS-2, the true width is believed to be in the region of 1.5 meters.

Complete assay results from the re-sampling of the two holes two drill holes are shown in Table 1

Mr. Matthews states “The assay results from the main antimony veins at Alto Sobrido are very encouraging. The upcoming drill program has been designed to intersect both the main antimony veins at depth and along strike some 60 meters to the west from the previously completed holes. The holes will also test the gold bearing structures noted from Kernow sampling. We will continue to use the assay methods for antimony (HBr/ICP) which has shown that antimony values may have been under estimated in certain areas of the project.”

About Antimony

Antimony is an industrial metal. It is used primarily in lead acid batteries, as a flame retardant and as a catalyst for PET’s (PolyEthylene Terephthalate). The current price for antimony ingots is \$2.55 (U.S.) per pound. One per cent antimony equates to 22 pounds per metric tonne.

Future exploration

Drill targets have been established and drilling is expected to commence in the New Year. Environmental base line studies have also been initiated.

Quality Control and Quality Assurance.

All samples for gold and antimony were completed at OMAC Labs. Ltd. in County Galway, Ireland (an ISO 17025 certified facility) using standard industry practices and conventional atomic absorption and fire assay methods for gold. Antimony assays were completed by GAR Aqua Regia Digestion and Flame AA finish. Over limit (>2.0% Sb) values were check assayed by OMAC method HBr/ICP a high precision analysis using ICP for base metals.

About Kernow

Kernow is a gold explorer based in Porto, Portugal, with a portfolio of prospective gold and copper/gold projects including the Jales/Gralheira project (49% Kernow), the Boticas project and the Alto Sobrido project. Global Minerals Ltd. can earn an initial 50% interest in the project with Kernow as the operator. (See News Release dated June 7, 2007).

The data contained in this News Release has been reviewed and verified by Kernows President, Alan F. Matthews, C.Eng., a “qualified person” for the purposes of National Instrument 43-101 *Standards of Disclosure for Mineral Projects*.

Contacts

For further information concerning Kernow’s activities please visit Kernow’s web site at www.kernowresources.com or contact Mr. Alan Matthews by telephone in Portugal at + (351) 93 676 0927 or by facsimile at + (351) 22 609 5185 or by e-mail at: piran@mindspring.com. Kernow has also engaged the services of First Canadian Capital Corporation Corp. and its principal, Mr. Jason Monaco, can be contacted at 416 742 5600 or 1 866 580 8891.

The TSX Venture Exchange does not accept responsibility for the adequacy or accuracy of the content of this news release.

This news release contains forward looking statements regarding the ongoing and upcoming exploration work and expected geometry of geological formations and structures. Actual results may differ materially from those currently anticipated in such statements

TABLE 1

Hole DDAS-1. Dip -45° Azimuth 311°, Depth 111.0 meters.

Kernow Sample number	From Meters	To Meters	Interval Meters	Gold g/t Connary	Gold g/t Kernow	Antimony % Connary	Antimony % Kernow
11 A	20.7	21.7	1.0	1.29	0.92	0.02	0.018
12 A	21.7	22.85	1.15	0.70	0.11	Not assayed	0.012
36 A	49.75	50.25	0.5	1.98	1.68	4.34	7.69
37 A	50.25	50.55	0.3	1.19	0.47	2.49	3.15
38 A	50.55	51.4	0.85	0.68	0.96	0.65	0.83
39 A	51.4	52.4	1.0	0.38	0.63	0.13	0.13
40 A	52.4	53.4	1.0	0.01	0.01	0.09	0.07
41 A	53.4	54.6	1.2	0.28	0.36	0.03	0.18
42 A	54.6	55.8	1.2	0.13	0.07	1.14	0.28
43 A	55.8	56.8	1.0	0.08	0.42	2.09	3.19
57 A	69.5	69.85	0.35	0.18	0.30	0.24	3.74
58 A	69.85	70.9	1.05	0.13	0.96	1.67	1.67
59 A	70.9	71.9	1.0	0.69	0.91	3.38	4.41
60 A	71.9	72.9	1.0	0.41	0.78	1.08	0.62
61 A	72.9	73.9	1.0	0.26	0.39	1.32	1.31
62 A	73.9	74.9	1.0	0.26	0.20	0.63	0.27
63 A	74.9	75.9	1.0	0.27	0.20	Not assayed	0.089
64 A	75.9	76.9	1.0	0.64	0.24	Not assayed	0.091
65 A	76.9	77.9	1.0	0.92	0.90	0.14	0.20
66 A	77.9	78.9	1.0	0.89	1.08	0.70	0.58
67 A	78.9	80.0	1.1	0.34	0.39	2.71	1.67
68 A	80.0	81.0	1.0	0.21	0.18	2.15	3.49
69 A	81.0	82.0	1.0	0.31	0.31	0.12	0.16
70 A	82.0	83.0	1.0	0.25	0.17	0.27	0.06
71 A	83.0	84.0	1.0	0.19	0.14	0.39	0.58
72 A	84.0	85.0	1.0	0.96	0.51	1.33	0.21

Hole DDAS-2. Dip -57° Azimuth 300°, Depth 77.95 meters.

Kernow Sample number	From Meters	To Meters	Interval Meters	Gold g/t Connary	Gold g/t Kernow	Antimony % Connary	Antimony % Kernow
2 A	4.15	5.1	0.95	0.32	0.30	Not assayed	0.07
3 A	5.1	6.2	1.1	0.49	0.49	Not assayed	0.11
4 A	6.2	7.4	1.2	1.50	1.82	Not assayed	0.27
5 A	7.4	8.5	1.1	1.81	2.04	Not assayed	0.32

Kernow Sample number	From Meters	To Meters	Interval Meters	Gold g/t Connary	Gold g/t Kernow	Antimony % Connary	Antimony % Kernow
6 A	8.5	9.5	1	0.55	0.71	Not assayed	0.06
7 A	9.5	10.4	0.9	0.03	0.06	Not assayed	0.02
29 A	33.55	34.55	1	0.07	0.05	0.04	0.02
30 A	34.55	35.35	0.8	0.09	0.06	0.38	0.22
31 A	35.35	35.75	0.4	0.72	0.39	>30.00	51.26
32 A	35.75	36.75	1.0	0.37	0.78	4.85	6.13
33 A	36.75	37.75	1.0	0.04	0.03	1.04	0.86
34 A	37.75	38.75	1.0	0.04	0.42	0.25	0.08
35 A	38.75	40.1	1.35	0.12	0.10	1.30	1.39
36 A	40.1	41.55	1.45	0.01	0.03	0.07	0.08
37 A	41.55	42.85	1.3	2.26	1.07	0.27	0.07
38 A	42.85	43.95	1.1	0.05	0.05	0.08	0.10
39 A	43.95	44.4	0.45	0.40	1.49	0.43	0.62
40 A	44.4	45.25	0.85	0.01	0.02	0.36	0.28

Those antimony assays noted in **bold** were subject to OMAC Laboratories Ltd. technique HBr/ICP (inductively coupled plasma). To date this method has consistently produced higher antimony grades than those previously noted.